

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 February 2001 (15.02.2001)

PCT

(10) International Publication Number
WO 01/10354 A1

(51) International Patent Classification⁷: A61F 2/16 (74) Agent: BROWN, Boniard, I.; 1500 West Covina Parkway, #113, West Covina, CA 91790 (US).

(21) International Application Number: PCT/US00/21722

(81) Designated States (national): CA, CN, JP.

(22) International Filing Date: 8 August 2000 (08.08.2000)

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(25) Filing Language: English

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

(26) Publication Language: English

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(30) Priority Data:


09/370,235 9 August 1999 (09.08.1999) US

(71) Applicant and

(72) Inventor: CUMMING, J., Stuart [US/US]; 1407 Emerald Bay, Laguna Beach, CA 92651 (US).



(54) Title: LENS FOR INCREASED DEPTH OF FOCUS



WO 01/10354 A1

(57) Abstract: An intraocular lens provides substantially increased depth of focus for accurate near and far vision with an optic (14) much thinner than a natural lens, and the lens being rigid, vaulted posteriorly and adapted for posterior positioning in the capsular bag (16). The optic is positioned substantially farther from the cornea (12) than a natural lens, so that a cone of light (3A) exiting the optic to impinge upon the retina is much smaller than a cone of light from a natural lens. Typically, the optic may be about 1.0 mm thick and its distance from the cornea 7.0-8.0 mm.

4

Description

LENS FOR INCREASED DEPTH OF FOCUS

Technical Field

5 A natural human optic typically has a thickness of about 5.0 mm. Light rays entering the cornea and passing to the optic typically travel about 7.0 to 8.0 mm. Light rays pass from the optic in a cone of light with its apex at the retina. The natural lens provides only a limited degree of depth 10 of focus with clear vision over a limited range of distances.

15 The present invention provides an optic which is only a fraction the thickness of the natural lens. Whereas the natural lens is about 5.0 mm thick, the lens of the invention may typically be 1.0 mm and may range from about 0.5 mm to 1.5 mm. The distance from the cornea to the optic of the invention is about 7.0-8.0 mm, whereas with a natural lens, the light rays travel only about 3.5 mm from cornea to optic. Light rays refracted by and exiting the optic define a cone 20 of light much smaller in cross-sectional area than the natural lens, and therefore impinge on the retina in a smaller area. The much smaller cone provides greatly increased depth of focus in comparison with a natural 25 lens, and thus enables clear vision over a long range of distances. In effect, the invention provides

effective accommodation as between near and far vision, and a person is enabled to view accurately over a wide range of distances. The optic is positioned much farther from the cornea than a natural 5 lens, and this increase of distance minimizes the distance optical power change. The further posterior the optic, the higher the power of the optic and the less movement required for a given power change. The lens according to the invention is rigid, the haptics 10 being rigidly connected to the optic, and the lens is vaulted posteriorly. Thus, the distance between the cornea and the optic is maximized and the distance of travel of light rays between cornea and optic is increased.

15 The rigid lens causes the optic to move with the periphery of the capsular bag in response to ciliary muscle changes, particularly for near vision.

Brief Description of Drawings

Figure 1 is a cross-sectional view of a 20 frontal portion of a human eye with a lens according to the invention disposed therein;

Figure 2 is a partial sectional view of an eye showing light rays entering the cornea and exiting the optic in a cone of light from a natural lens to 25 the retina;

Figure 3 is a view similar to that of Figure

2, showing an optic according to the invention, and light rays exiting the optic in a cone of light of smaller size than with the natural lens of Figure 2;

5 Figures 4 and 5 are sectional views taken respectively at line 4-4 and line 5-5 in Figure 1, showing a capsular bag and haptic in relation to the ciliary muscle in near and far vision positions of the capsular bag and haptic;

10 Figure 6 is a diagrammatic sectional view of the ciliary muscle and capsular bag showing in solid lines their near vision positions, and showing in broken lines their far vision positions;

15 Figure 7 is an elevational view of a preferred embodiment of lens and haptic according to the invention;

Figure 8 is a side elevational view of the lens of Figure 7;

20 Figure 9 is an elevational view of another preferred embodiment of lens according to the invention; and

Figure 10 is a side elevational view of the lens of Figure 9.

Best Mode For Carrying Out the Invention:

25 The present invention provides substantially increased depth of focus, for effective near and far accurate vision by providing a thin optic which is

only a fraction the thickness of a natural lens or a conventional artificial lens optic, and by providing a rigid lens adapted to be positioned posteriorly in the natural capsular bag.

5 Referring to the drawings, Figure 1 is a cross-sectional view of an eye 10 with a cornea 12, with a lens 14 according to the invention disposed in the capsular bag 16 of the eye. As indicated in Figure 2, light rays entering at the cornea are 10 refracted and impact a natural lens 14 which refracts the rays to define a cone of light which impacts the retina. Figure 3 is a partial sectional view showing a thin optic 18 of the invention disposed substantially farther posteriorly than the natural 15 lens 14 (or a conventional artificial lens) of 5 mm thickness (d_2 in Figure 2). The light rays passing from the cornea to the optic 18 must travel a distance of about 7.0 to 8.0 mm from the cornea to the optic, whereas with the natural lens 14 light rays travel 20 only about 3.5 mm. The light rays refracted by and exiting the optic 18 define a cone of light of much smaller cross-sectional area (Figure 3A) impact the retina in a smaller area, in comparison with the much larger cone of light and its much larger cross section 25 (Figures 2 and 2A). An optic according to the invention may typically be 1.0 mm thick (d_1 in Figure 3), and may range from about 0.5 to about 1.5 mm in

thickness.

The much smaller cone of light provides greatly increased depth of focus, thus enabling clear vision over a long range of distances, in comparison 5 with the much larger cone of light produced by the natural human lens or conventional artificial intraocular lens. The much improved depth of focus provides effective accommodation or "pseudo accommodation", as between near and far vision, so 10 that a person is enabled to view accurately over a wide range of distances. The increase of distance which light rays must travel between the cornea and the optic minimizes the distance optical power change -- i.e., the further posterior the optic, the higher 15 the power of the optic and the less movement required for significant power change.

The lens 14 according to the invention is rigid, with the haptics thereof rigidly connected with the optic. The lens is vaulted posteriorly, as shown 20 in Figs. 1 and 8, in order to maximize the posterior positioning of the optic to increase the distance of travel of light rays between the cornea and the optic. Additional rigidity may be provided by rigid bars 20 25 secured along the edges of the lens (Figure 7) or as shown in Figure 9, a lens 22 may have rigid bars 24 disposed inwardly of the lens edges with arcuate portions extending about the optic, as shown. The

haptics are preferably flexible to enable folding for insertion of the lens into the human eye via a slot therein of relatively short length. Lenses according to the invention may preferably embody upper and lower 5 flexible loop portions 26, 26 (Figure 7) which extend oppositely to facilitate lens rotation during insertion into an eye, without interfering engagement with the capsular bag.

10 The outer peripheral equator portion of the capsular bag is moved in response to configurational changes in the ciliary muscle as between near and far vision, thereby causing the lens and its optic to move with the periphery of the capsular bag in response to such muscle changes, particularly with respect to near 15 vision. That is, upon contraction of the ciliary muscle, anterior displacement of the capsular bag equator effects corresponding anterior movement of the optic. The lens and optic are free to move anteriorly because of the relative stiffness of the anterior bag 20 resulting from leather-like fibrosis or dead tissue arising from conventional surgical cutting to remove the anterior portion of the bag. The lens is moved posteriorly only when the muscle acts thereon.

25 Figures 4, 5 and 6 are diagrammatic cross-sectional views of the ciliary muscle 28 of the eye in relation to the peripheral or equator portion of the capsular bag with the lens 14 of the invention

therein. Figure 6 shows in broken lines the configuration 30 of the muscle 28 and the relative position of the haptic 14, in a far vision position, and showing in solid lines 32, the muscle configuration 30 and relative position of the haptic for near vision. Muscle configuration indicated at 30 extends into vitreous cavity, thus increasing pressure to a limited degree to further aid in moving the lens anteriorly. Muscle constriction moves the rigid lens forward to a limited degree at the bag periphery, the whole lens moving forwardly.

10 Thus there has been shown and described a lens for increased depth of focus which fulfills all the objects and advantages sought therefor. Many changes, 15 modifications, variations and other uses and applications of the subject invention will, however, become apparent to those skilled in the art after considering this specification together with the accompanying drawings and claims. All such changes, 20 modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention which is limited only by the claims which follow.

Claims

1. An intraocular lens for increased depth of focus, comprising:
 - an optic having a thickness substantially less than a natural human lens, and
 - 5 at least two haptics connected with the optic,
 - said lens being adapted to be posteriorly positioned in the capsular bag of the eye,
 - 10 whereby light refracted by the cornea travels substantially farther to the optic than with a natural optic and a substantially smaller cone of light passes from the optic to the retina to provide substantially increased depth of
 - 15 focus.
2. A lens according to Claim 1, wherein the optic is about 1.0 mm in thickness.
3. A lens according to Claim 1, wherein the optic has a thickness between 0.05 mm and 1.5 mm.
- 20 4. A lens according to Claim 1, wherein the lens is rigid and the haptics are rigidly connected with the optic and extend therefrom.

5. A lens according to Claim 1, wherein the lens is configurated to vault posteriorly in the capsular bag of the eye.
- 5 6. A lens according to Claim 4, wherein the lens is configurated to vault posteriorly in the capsular bag.
7. A lens according to Claim 4, wherein the optic has a thickness between 0.50 mm and 1.5 mm.
- 10 8. A lens according to Claim 5, wherein the optic has a thickness between 0.50 mm and 1.5 mm.
- 15 9. A lens according to Claim 4, wherein: the rigid lens is moved anteriorly for near vision and posteriorly for far vision by changes in ciliary muscle configuration during contraction.
10. A lens according to Claim 9, wherein: a peripheral equator of the capsular bag and the rigid lens therein are moved about 1.0 mm between their far and near vision positions, whereby the optic is positioned about 1.0 mm further anteriorly than posteriorly to provide improved near vision.

11. A lens according to Claim 9, wherein:

redistribution of ciliary muscle mass upon
constriction of the muscle for near vision causes
encroachment thereof on the vitreous cavity and
an increase of pressure therein to aid in urging
the rigid lens anteriorly to enhance near vision.

5

12. An intraocular lens for increased depth of focus,
comprising:

10

an optic having a thickness substantially
less than the thickness of a natural human lens,
and

two haptics rigidly connected to the optic
and extending therefrom,

15

said lens being configurated to vault
posteriorly in the capsular bag to position the
optic farther from the cornea of the eye,

20

whereby light refracted by the cornea
travels substantially farther to the optic than
with a natural optic and a substantially smaller
cone of light passes from the optic to the retina
to provide substantially increased depth of
focus.

13. A lens according to Claim 12, wherein the optic
has a thickness between 0.05 mm and 1.5 mm.

14. A lens according to Claim 12, wherein:

the rigid lens is moved anteriorly for near vision and posteriorly for far vision by changes in ciliary muscle configuration during contraction.

5

15. A lens according to Claim 13, wherein:

the rigid lens is moved anteriorly for near vision and posteriorly for far vision by changes in ciliary muscle configuration during contraction.

10

16. A lens according to Claim 14, wherein:

redistribution of ciliary muscle mass upon constriction of the muscle for near vision causes encroachment thereof on the vitreous cavity and an increase of pressure therein to aid in urging the rigid lens anteriorly to enhance near vision.

15

17. A lens according to Claim 14, wherein:

a peripheral equator of the capsular bag and the rigid lens therein are moved about 1.0 mm between their far and near vision positions, whereby the optic is positioned about 1.0 mm further anteriorly than posteriorly to provide improved near vision.

20

18. A lens according to Claim 12, wherein:

a peripheral equator of the capsular bag and
the rigid lens therein are moved about 1.0 mm
between their far and near vision positions,
5 whereby the optic is positioned about 1.0 mm
further anteriorly than posteriorly to provide
improved near vision.

19. A lens according to Claim 4, and further

10 comprising at least one rigid bar secured to and
extending longitudinally of the lens to provide
rigidity.

20. A lens according to Claim 19, wherein said lens
is longitudinally flexible for bending for
insertion into an eye.

15 21. A lens according to Claim 12, and further

comprising at least one rigid bar secured to and
extending longitudinally of the lens to provide
rigidity.

22. A lens according to Claim 21, wherein said lens

20 is longitudinally flexible for bending for
insertion into an eye.

23. A lens according to Claim 21, wherein two rigid

bars are disposed in spaced relation and extend longitudinally of the lens.

1/2




FIG. 1




FIG. 2



FIG. 2A




FIG. 3



FIG. 3A




FIG. 4




FIG. 6




FIG. 5




FIG. 7



FIG. 8




FIG. 9



FIG. 10

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/21722

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61F 2/16
US CL : 623/6.37

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 623/6.37

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST: Derwent and JPO: vault, accommodate, cone, conical, thin, thick, narrow, slim, slender

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,409,691 A (LEVY) 18 October 1983 (18.10.1983): figures; column 1, lines 18-22; column 2, lines 5-6, 21-30, and 33-35.	1, 5, 12, 14, 16-18
---		-----
Y		2-4, 6-11, 13, 15
X	US 4,657,540 .. (SHEARING) 14 April 1987 (14.04.1987): entire document.	1-4, 12, 13, 19-23
Y	RU 2034522 C1 (SHURKIN) 10 May 1995 (10.05.1995): English abstract; figures.	1-8, 12, 13

<input type="checkbox"/>	Further documents are listed in the continuation of Box C.	<input type="checkbox"/>	See patent family annex.
*	Special categories of cited documents:	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A"	document defining the general state of the art which is not considered to be of particular relevance	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step
"E"	earlier application or patent published on or after the international filing date	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means		
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search 10 October 2000 (10.10.2000)	Date of mailing of the international search report 03 JAN 2001
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. 703-305-3230	Authorized officer D. WILLSE Telephone No.